

View Online at https://aerobasegroup.com/nsn/5910-01-036-1072

Body Style:
Rotary
Overall Height:
0.310 inches
Overall Diameter:
0.375 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Center To Center Distance Between Terminals Parallel To Diameter:
0.300 inches
Quality Factor At 25 Deg Celsius:
500.0
Inclosure Type:
Encased
Adjustment Device Rotation:
1.0 turns counterclockwise
Adjustment Device Torque:
Between 1.000 inch-ounces and 6.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
10.0 gigohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Capacitance Range In Picofarads:
+2.0/+8.0 single section
Nonderated Voltage Rating And Type:
350.0 dc continuous single section
Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:
-4.50/+2.00 single section and -2.50/+0.50 single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.50 single section
Terminal Type And Quantity:
2 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5910-01-036-1072

Ceramic Dielectric Variable Capacitor - Page 2 of 2

Fiig: A096a0

