## NSN 5910-01-036-3577

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-036-3577 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.250 inches **Body Diameter:** 0.625 inches **Body Length:** 1.125 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 470.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 35.0000 Dc Leakage At Reference Temp: 35.000 microamperes **Case Insulation Material:** Rubber **Test Data Document:** 81349-mil-c-39018/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5910-01-036-3577

Electrolytic Fixed Capacitor - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A010b0