NSN 5910-01-036-7921

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-036-7921

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.290 inches
Body Width:
0.110 inches
Body Height:
0.220 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Polarized
Capacitance Value Per Section:
6.800 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
25.0 dc single section Tolerance Range Per Section:
-
Tolerance Range Per Section:
Tolerance Range Per Section: -10.00/+10.00 percent single section
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 2.000 microamperes
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 2.000 microamperes Terminal Surface Treatment:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 2.000 microamperes Terminal Surface Treatment: Solder
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 2.000 microamperes Terminal Surface Treatment: Solder Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 2.000 microamperes Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead

--

NSN 5910-01-036-7921

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0