## NSN 5910-01-037-4102

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-037-4102
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
Between 1.250 inches and 1.750 inches
Body Diameter:
Between 0.119 inches and 0.151 inches
Body Length:
Between 0.255 inches and 0.317 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
8.0 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
2.000
Dc Leakage At Reference Temp:
0.600 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Diagtia

idotio

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-037-4102

Electrolytic Fixed Capacitor - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0