## NSN 5910-01-039-1299

Mica Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-039-1299 **Thread Class:** 2a **Body Style:** Compression **Terminal Length:** 0.281 inches **Bushing Diameter:** 0.216 inches **Bushing Length:** 0.500 inches **Body Length:** 0.938 inches **Body Width:** 0.875 inches **Body Height:** 0.344 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.406 inches **Dissipation Factor At 25 Deg Celsius In Percent:** 0.004 **Terminal Width:** 0.203 inches **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 40 **Nonderated Operating Temp:** Between -35.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.216 inches **Capacitance Range In Picofarads:** 

+1000.0/+2155.0 single section

**Nonderated Voltage Rating And Type:** 

500.0 dc continuous single section

## NSN 5910-01-039-1299

Mica Dielectric Variable Capacitor - Page 2 of 2



Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A096a0