NSN 5910-01-039-2222

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-039-2222

Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.380 inches
Body Length:
1.150 inches
Body Width:
1.100 inches
Body Height:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.440 inches
Schematic Diagram Designator:
Delta connected
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Section Quantity:
3
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.039 microfarads all sections
Nonderated Operating Temp:
Between 0.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 ac-rms all sections
Tolerance Range Per Section:
-5.00/+5.00 percent all sections
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.700
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5910-01-039-2222

Plastic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0