## NSN 5910-01-039-4529

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-039-4529

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Mil-std-1276 Wire Lead Type Designator:
N.1
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.500 inches
Body Width:
0.300 inches
Body Height:
0.500 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.500 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section
-15.0/+15.0 without voltage applied single section
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Type And Quantity:
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Type And Quantity: 2 uninsulated wire lead
-15.0/+15.0 without voltage applied single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 70.0 ac-rms single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:

No

Demilitarization:

## NSN 5910-01-039-4529

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0