# NSN 5910-01-040-0420

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-040-0420

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

# **Terminal Length:**

0.281 inches

#### **Body Diameter:**

3.032 inches

#### **Body Length:**

5.157 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

1.250 inches

#### **Terminal Diameter:**

0.190 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Impedance At Minimum Operating Tempurature In Ohms:

0.4

#### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

6800.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

7.2 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### Case Material:

Metal

# Capacitive Electrode Material:

Aluminum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

0.03

#### Dc Leakage At Reference Temp:

1.200 microamperes

## **Case Insulation Material:**

Plastic

#### **Test Data Document:**

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5910-01-040-0420

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 threaded hole

# Specification Data:

81349-mil-c-0039018/4 government specification

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0