

View Online at <https://aerobasegroup.com/nsn/5910-01-040-7576>

Body Style:

Rotary

Terminal Length:

0.094 inches

Body Length:

0.854 inches

Body Width:

0.656 inches

Body Height:

0.375 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Quality Factor At 25 Deg Celsius:

400.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.437 inches

Inclosure Type:

Encased

Adjustment Device Torque:

Between 4.000 inch-ounces and 20.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+11.0/+110.0 single section

Nonderated Voltage Rating And Type:

500.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

+6.00/+16.00 single section and -11.00/-6.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.75 single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0