

View Online at <https://aerobasegroup.com/nsn/5910-01-042-0084>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.250 inches

Terminal Length:

0.625 inches

Body Length:

0.530 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unef

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

0.100 microfarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-0.00/+100.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

500.0 megohms

Dissipation Factor At Reference Temperature In Percent:

5.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0