Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-042-1219

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.800 inches

Body Width:

0.550 inches

Body Height:

0.250 inches

Center To Center Distance Between Terminals Parallel To Length:

0.375 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

1500.0 megohm-microfarads

Capacitance Value Per Section:

4700.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.7500

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyester

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0