## NSN 5910-01-043-3440

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-043-3440 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.352 inches **Body Length:** 0.842 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 2500.0 megohm-microfarads **Capacitance Value Per Section:** 0.012 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 170.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 250000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.0500 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polytetrafluoroethylene **Case Insulation Material:** 

**Plastic** 

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-043-3440

Plastic Dielectric Fixed Capacitor - Page 2 of 2



SI	1e	lf	Ιi	fe:
Ο.	···	•••	_,	٠٠.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0