NSN 5910-01-043-6907

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-043-6907

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 1.0000 **Terminal Length:** 1.500 inches **Body Diameter:** 0.670 inches **Body Length:** 1.625 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 5000.0 megohm-microfarads **Capacitance Value Per Section:** 0.470 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 300.0 ac-rms single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Test Data Document:** 81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39022/7 government specification

Shelf Life:

N/a

NSN 5910-01-043-6907

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A010b0