NSN 5910-01-044-1649

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-044-1649 **Body Style:** Piston **Overall Length:** 0.468 inches **Body Length:** 0.281 inches **Overall Diameter:** 0.220 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -15.0/+15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.266 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.156 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **Inclosure Type: Encased Tuning Characteristic:** Straight line capacity single section Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.6/+6.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Test Data Document:** 98230-0n228078-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a

--

Unit Of Measure:

NSN 5910-01-044-1649

Air Dielectric Variable Capacitor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A096a0