Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-045-2913

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Not established

# **Terminal Length:**

0.500 inches

## **Body Length:**

1.240 inches

### **Body Width:**

0.580 inches

#### **Body Height:**

### 0.400 inches

### Center To Center Distance Between Terminals Parallel To Length:

1.110 inches

### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

0.180 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

500000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1000

# **Terminal Surface Treatment:**

Solder

# **Dielectric Material:**

Plastic polystyrene

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0