## NSN 5910-01-046-6867

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-046-6867
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.580 inches
Body Width:
0.180 inches
Body Height:
0.270 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Insulation Resistance At Maximum Operating Temp:
20000.0 megohm-microfarads
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-120.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Solder
Dielectric Material:

Plastic polystyrene

## NSN 5910-01-046-6867

Plastic Dielectric Fixed Capacitor - Page 2 of 2



<b>Terminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0