NSN 5910-01-047-4674

W/mtg tabs/flanges, terminal (s) on one surface

Body Style:

Reliability Indicator:

Terminal Type And Quantity:

13 tab, solder lug

Not established

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-047-4674

| Terminal Length: |
|--|
| 0.375 inches |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 1.563 inches |
| Body Height: |
| 1.188 inches |
| Continuous Current Rating In Amps: |
| 1.0 |
| Unthreaded Mounting Hole Diameter: |
| 0.178 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 3.500 inches |
| Mounting Facility Type And Quantity: |
| 2 unthreaded mounting holes |
| Section Quantity: |
| 10 |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 20.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 1.000 microfarads all sections |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 105.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 250.0 dc 9th section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent all sections |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 2000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.000 |

NSN 5910-01-047-4674

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A010b0