Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-047-6969

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.406 inches

#### **Body Length:**

1.484 inches

# **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### **Electrical Polarization:**

Polarized

#### **Features Provided:**

Hermetically sealed case

#### **Capacitance Value Per Section:**

4.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

#### **Tolerance Range Per Section:**

-15.00/+15.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Tantalum

#### **Dissipation Factor At Reference Tempurature In Percent:**

10.0000

## Dc Leakage At Reference Temp:

16.000 microamperes

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-3965/15 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

# NSN 5910-01-047-6969

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0