Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-049-1253

# **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

# **Reliability Indicator:**

Not established

# **Terminal Length:**

0.700 inches

# **Body Length:**

6.440 inches

#### **Body Width:**

6.270 inches

**Body Height:** 

### 7.300 inches

**Terminal Diameter:** 

0.250 inches

### **Unthreaded Mounting Hole Diameter:**

0.150 inches and 0.348 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

6.880 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.460 inches

# Mounting Facility Type And Quantity:

10 unthreaded mounting holes

# **Features Provided:**

Hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

10.0 megohms

# Capacitance Value Per Section:

75.000 microfarads single section

# Nonderated Operating Temp:

Between -10.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

# **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

# Case Material:

Metal

# Insulation Resistance At Reference Temp:

100.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

1.0000



# Terminal Type And Quantity:

1 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0