NSN 5910-01-049-2184

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-049-2184

| view Online at https://aerobasegroup.com/nsn/5910-01-049-2184 | | |
|--|--|--|
| Body Style: | | |
| W/o mtg facilities terminal (s) on one surface | | |
| Reliability Indicator: | | |
| Not established | | |
| Terminal Length: | | |
| 1.250 inches | | |
| Body Length: | | |
| 0.500 inches | | |
| Body Width: | | |
| 0.280 inches | | |
| Body Height: | | |
| 0.125 inches | | |
| Center To Center Distance Between Terminals Parallel To Length: | | |
| 0.400 inches | | |
| Terminal Diameter: | | |
| 0.020 inches | | |
| Schematic Diagram Designator: | | |
| No common or grounded electrode (s) | | |
| Capacitance Value Per Section: | | |
| 1200.000 picofarads single section | | |
| Nonderated Operating Temp: | | |
| Between -55.0 degrees celsius and 85.0 degrees celsius | | |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: | | |
| 0.0 single section | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | |
| 50.0 dc single section | | |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: | | |
| -50.0/+50.0 single section | | |
| Tolerance Range Per Section: | | |
| -5.00/+5.00 percent single section | | |
| Case Material: | | |
| Plastic | | |
| Insulation Resistance At Reference Temp: | | |
| 1000000.0 megohms | | |
| Dissipation Factor At Reference Tempurature In Percent: | | |
| 0.1500 | | |
| Terminal Surface Treatment: | | |
| Solder | | |
| Dielectric Material: | | |
| Plastic | | |

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-01-049-2184

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| She | lf I | Life: |
|-----|------|-------|
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0