NSN 5910-01-049-5679

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-049-5679 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.750 inches **Body Diameter:** Between 0.453 inches and 0.515 inches **Body Length:** Between 1.500 inches and 1.562 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohm-microfarads **Capacitance Value Per Section:** 0.680 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 440.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -440.0/+440.0 single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 10000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyester **Terminal Type And Quantity:**

2 uninsulated wire lead

NSN 5910-01-049-5679

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0