NSN 5910-01-050-4226

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-050-4226 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.937 inches **Bushing Diameter:** 0.190 inches First Flat Length: 0.125 inches single shaft Flat Height: 0.162 inches single shaft and 0.172 inches single shaft **Shaft Diameter:** 0.191 inches single shaft and 0.195 inches single shaft **Bushing Length:** Between 0.250 inches and 0.312 inches **Shaft Length:** 0.125 inches single shaft **Body Length:** 0.500 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -150.0/+150.0 single section **Quality Factor At 25 Deg Celsius:** 750.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Bushing Shape:** Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 100.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size: 0.190 inches

NSN 5910-01-050-4226

Glass Dielectric Variable Capacitor - Page 2 of 2



Shaft Type:
Round, slotted, flatted single shaft
Capacitance Range In Picofarads:
+1.0/+16.0 single section
Nonderated Voltage Rating And Type:
1000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0