

View Online at <https://aerobasegroup.com/nsn/5910-01-051-3217>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.400 inches

Terminal Length:

0.453 inches

Body Length:

1.203 inches

Continuous Current Rating In Amps:

3.2

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

2000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-22.0/+56.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

7500.0 megohm-microfarads

Power Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Precious Material And Location:

Bushing silver

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0