Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-051-8911

|   | Body Style:<br>N/o mtg facilities, axial terminals         |
|---|--|
|   | Reliability Indicator:                                     |
|   | Not established  |
|   | Schematic Diagram Designator:                              |
|   | Electrod (s) grounded to case, w/gnd terminal              |
|   | Electrical Polarization:                                   |
|   |  |
| - |  |
|   | Capacitance Value Per Section:                             |
|   | 50.000 microfarads single section                          |
|   | Nonderated Operating Temp:                                 |
|   | Between -85.0 degrees celsius and 85.0 degrees celsius     |
|   | Nonderated Continuous Voltage Rating And Type Per Section: |
|   | 75.0 dc single section                                     |
|   | Followance Range Per Section:                              |
|   | 20.00/+20.00 percent single section                        |
|   | Case Material:   |
|   | Metal  |
|   | Capacitive Electrode Material:                             |
|   | Fantalum   |
| ( | Case Insulation Material:                                  |
|   | Plastic  |
|   | Ferminal Type And Quantity:                                |
| 2 | 2 uninsulated wire lead                                    |
| S | Shelf Life:  |
| ٢ | N/a  |
| ι | Jnit Of Measure:   |
| - | -  |
| C | Demilitarization:  |
| ٢ | No   |
| F | Filg:  |
| , | A010b0   |