NSN 5910-01-052-7204

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-052-7204

Body Style: W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.750 inches **Body Diameter:** 0.225 inches **Body Length:** 0.425 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.125 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 33.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 30.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 6.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 8.0000 Dc Leakage At Reference Temp: 3.000 microamperes

Terminal Surface Treatment: Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-01-052-7204

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0