Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-052-9143

# Body Style:

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

## **Reliability Failure Rate Level In Percent:**

0.0001

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.188 inches

**Body Length:** 

0.453 inches

#### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

## Electrod (s) grounded to case

**Electrical Polarization:** 

Nonpolarized

## **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

22.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Tantalum

# Dissipation Factor At Reference Tempurature In Percent:

8.3000

## **Case Insulation Material:**

Plastic

## **Special Features:**

Sealed in a single silver case

## **Test Data Document:**

98230-0n241721-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

# NSN 5910-01-052-9143

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0