

View Online at https://aerobasegroup.com/nsn/5910-01-053-9788

#### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

#### **Body Diameter:**

0.207 inches

**Body Length:** 

0.812 inches

**Terminal Diameter:** 

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

## Capacitance Value Per Section:

2200.000 picofarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.6000

**Case Insulation Material:** 

Plastic

# Test Data Document:

81349-mil-c-19978/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-01-053-9788

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

