NSN 5910-01-055-2732

Body Style:

Solder

Test Data Document:

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-055-2732

W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
4.562 inches
Body Width:
3.750 inches
Body Height:
7.500 inches
Center To Center Distance Between Terminals Parallel To Length:
2.000 inches
Terminal Diameter:
0.190 inches
Terminal Height From Body:
2.750 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Features Provided: Hermetically sealed case
Hermetically sealed case
Hermetically sealed case Insulation Resistance At Maximum Operating Temp:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:
Hermetically sealed case Insulation Resistance At Maximum Operating Temp: 15.0 megohm-microfarads Capacitance Value Per Section: 1.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6000.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 1500.0 megohm-microfarads

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-055-2732

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 standoff, threaded stud
Specification Data:
81349-mil-c-19978/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0