

View Online at <https://aerobasegroup.com/nsn/5910-01-055-5620>

**Body Style:**

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.0001

**Terminal Length:**

0.250 inches

**Body Diameter:**

Between 0.985 inches and 1.015 inches

**Body Length:**

Between 2.579 inches and 2.671 inches

**Continuous Current Rating In Amps:**

20.0

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

0.470 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.438 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

330.0 ac-rms single section and 1000.0 dc single section

**Tolerance Range Per Section:**

-0.20/+20.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100.0 megohms

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0