

View Online at <https://aerobasegroup.com/nsn/5910-01-055-5620>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0001

Terminal Length:

0.250 inches

Body Diameter:

Between 0.985 inches and 1.015 inches

Body Length:

Between 2.579 inches and 2.671 inches

Continuous Current Rating In Amps:

20.0

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.470 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.438 inches

Nonderated Continuous Voltage Rating And Type Per Section:

330.0 ac-rms single section and 1000.0 dc single section

Tolerance Range Per Section:

-0.20/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100.0 megohms

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0