NSN 5910-01-056-2164



Ceramic Dielectric Fixed Capacitor - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5910-01-056-2164 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 1.0000 **Terminal Length:** 1.500 inches **Body Diameter:** 0.090 inches **Body Length:** 0.160 inches **Terminal Diameter:** Between 0.015 inches and 0.027 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 68.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -25.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Test Data Document:** 81349-mil-c-39014/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

-- **Demilitarization:**No

Unit Of Measure:

Fiig:

N/a

A010b0