## NSN 5910-01-056-3530

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-056-3530 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.500 inches **Body Diameter:** 1.062 inches **Body Length:** 3.873 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** Feedthrough **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 0.059 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1300.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Dc Leakage At Maximum Operating Temp: 940.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 156.000 microamperes **Terminal Surface Treatment:** 

Solder **Case Insulation Material: Plastic** 

## NSN 5910-01-056-3530

Electrolytic Fixed Capacitor - Page 2 of 2



<b>Terminal</b>	<b>Type</b>	And	Quantity:
-----------------	-------------	-----	-----------

4 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0