

View Online at https://aerobasegroup.com/nsn/5910-01-058-9237

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.150 inches

**Body Length:** 

0.400 inches

**Terminal Diameter:** 

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

7000.0 megohms

#### **Capacitance Value Per Section:**

0.010 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

1000000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.3000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-0055514/4 government specification

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0