

View Online at https://aerobasegroup.com/nsn/5910-01-059-4005

Body St	yle:
Chip typ	e
Reliabili	ity Indicator:
Not esta	blished
Body Le	ength:
0.080 in	ches
Body W	idth:
0.050 in	ches
Body He	eight:
0.050 in	ches
Schema	tic Diagram Designator:
No comr	non or grounded electrode (s)
Capacit	ance Value Per Section:
30.000 p	vicofarads single section
Nondera	ated Operating Temp:
Betweer	1-55.0 degrees celsius and 125.0 degrees celsius
Tempur	ature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 singl	e section
Nondera	ated Continuous Voltage Rating And Type Per Section:
50.0 dc :	single section
Toleran	ce Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+3	0.0 single section
Toleran	ce Range Per Section:
-2.00/+2	.00 percent single section
Case Ma	aterial:
Ceramic	
Insulatio	on Resistance At Reference Temp:
100000.	0 megohms
Dissipat	tion Factor At Reference Tempurature In Percent:
0.1000	
Termina	al Type And Quantity:
2 bondin	ng pad
Shelf Li	fe:
N/a	
Unit Of	Measure:
Demilita	arization:
No	
Fiig:	
A010b0	