NSN 5910-01-059-6707

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



raper-plastic Dielectric Metallized Fixed Capacitor - rage 1 of 2
View Online at https://aerobasegroup.com/nsn/5910-01-059-6707
Body Style:
W/thd mtg studs, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.562 inches
Body Length:
1.406 inches
Terminal Diameter:
0.032 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.750 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:

0.136 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Power Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-059-6707

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0