

View Online at https://aerobasegroup.com/nsn/5910-01-059-9732

| Body Style: | |
|---|-----|
| Chip type | |
| Reliability Indicator: | |
| lot established | |
| Body Length: | |
| .080 inches | |
| Body Width: | |
| .050 inches | |
| Body Height: | |
| .050 inches | |
| Schematic Diagram Designator: | |
| lo common or grounded electrode (s) | |
| Capacitance Value Per Section: | |
| .300 picofarads single section | |
| Ionderated Operating Temp: | |
| Between -55.0 degrees celsius and 125.0 degrees celsius | |
| empurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsiu | us: |
| 0.0 single section | |
| Ionderated Continuous Voltage Rating And Type Per Section: | |
| 0.0 dc single section | |
| olerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: | |
| 30.0/+30.0 single section | |
| olerance Range Per Section: | |
| 0.25/+0.25 picofarads single section | |
| Case Material: | |
| Ceramic | |
| nsulation Resistance At Reference Temp: | |
| 00000.0 megohms | |
| Dissipation Factor At Reference Tempurature In Percent: | |
| .1000 | |
| erminal Type And Quantity: | |
| bonding pad | |
| Shelf Life: | |
| l/a | |
| Init Of Measure: | |
| | |
| Demilitarization: | |
| lo | |
| iig: | |
| 010b0 | |