

View Online at https://aerobasegroup.com/nsn/5910-01-059-9750

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

## **Terminal Length:**

1.625 inches

## **Body Diameter:**

0.572 inches

**Body Length:** 

1.375 inches

**Terminal Diameter:** 

0.040 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

# **Capacitance Value Per Section:**

0.330 microfarads single section

# Nonderated Operating Temp:

Between -65.0 degrees celsius and 100.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

**Case Insulation Material:** 

Plastic

# Test Data Document:

81349-mil-c-83421/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0