Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-061-1448

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.193 inches

**Body Length:** 

0.687 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

## **Capacitance Value Per Section:**

22000.000 picofarads single section

## **Nonderated Operating Temp:**

Between -65.0 degrees celsius and 100.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## Case Material:

Metal

## Insulation Resistance At Reference Temp:

1000000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

## **Case Insulation Material:**

Plastic

## **Test Data Document:**

81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-83421/1 government specification

## Shelf Life:

N/a

Unit Of Measure:

- ---
- Demilitarization:

No

# NSN 5910-01-061-1448

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

