NSN 5910-01-062-0513

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-062-0513
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.150 inches
Body Width:
0.100 inches
Body Height:
0.150 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
20.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 1000.0000
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 1000.0000 Terminal Surface Treatment:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 1000.0000 Terminal Surface Treatment: Solder
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -600.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 1000.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity:

--

Unit Of Measure:

NSN 5910-01-062-0513

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0