## NSN 5910-01-062-3361

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-062-3361

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.3000

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

**Body Length:** 

Between 0.285 inches and 0.295 inches

**Body Width:** 

Between 0.315 inches and 0.325 inches

**Body Height:** 

Between 0.140 inches and 0.150 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

0.200 inches

**Terminal Diameter:** 

0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

100000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-50.0/+150.0 single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

3.0000

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-062-3361

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0