NSN 5910-01-062-6277

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-062-6277

Body Style:

W/mtg bracket, axial terminals

Reliability Indicator:

Not established

Terminal Length:

Between 0.234 inches and 0.358 inches

Body Diameter:

Between 0.745 inches and 0.765 inches

Body Length:

Between 1.781 inches and 1.843 inches

Continuous Current Rating In Amps:

1.0

Unthreaded Mounting Hole Diameter:

0.156 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

1 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

6.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Power Factor At Reference Tempurature In Percent:

1.000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyester

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-01-062-6277

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0