

View Online at <https://aerobasegroup.com/nsn/5910-01-063-2373>

Body Style:

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0001

Terminal Length:

Between 0.110 inches and 0.120 inches

Body Length:

Between 0.320 inches and 0.325 inches

Body Width:

190.000 inches

Body Height:

0.105 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Electrical Polarization:

Nonpolarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

12.000 microfarads single section

Nonderated Operating Temp:

Between 0.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

0.0600

Case Insulation Material:

Plastic

Special Features:

Radiographic inspected, ea item assigned unique serial no.

Test Data Document:

98230-0n228028-16 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0