## NSN 5910-01-063-9111

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-063-9111

view Online at https://aerobasegroup.com/hsh/3310-01-003-3111
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.0001
Terminal Length:
Between 1.250 inches and 1.500 inches
Body Diameter:
0.185 inches
Body Length:
0.610 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
Electrod (s) grounded to case
Electrical Polarization:
Nonpolarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
20.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.0000
Case Insulation Material:
Plastic
Special Features:
Radiographic inspected, ea item assigned unique serial no.
Test Pata Decument:

## **Test Data Document:**

98230-0n228034-9 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## NSN 5910-01-063-9111

Electrolytic Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0