

View Online at <https://aerobasegroup.com/nsn/5910-01-064-4075>

**Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.250 inches

**Body Diameter:**

0.200 inches

**Body Length:**

0.400 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.250 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

B-52 aircraft support equipment. General purpose electronic test equipment (gpete). Ballistic missile early warning sys. (bmews). Oliver perry class ffg, sirius class t-afs 8, spruance class dd (963), kilauea class t-ae 26, forrestal class cv, whidbey island class lsd, austin ship class lpd-4 amphibious transport docks.

**Capacitance Value Per Section:**

12.000 picofarads single section

**Nonderated Operating Temp:**

85.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

-1500.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-250.0/+250.0 single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

10000.0 megohms

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0