

View Online at https://aerobasegroup.com/nsn/5910-01-064-6770

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Established

#### **Reliability Failure Rate Level In Percent:**

0.1000

#### **Terminal Length:**

1.250 inches

#### **Body Length:**

0.190 inches

#### **Body Width:**

0.190 inches

#### **Body Height:**

0.090 inches

#### Center To Center Distance Between Terminals Parallel To Length:

# 0.200 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

## Capacitance Value Per Section:

0.100 microfarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between 55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

2.5000

# **Test Data Document:**

98230-0n225133-5 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0