## NSN 5910-01-064-9105

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5010-01-06/L0105

| View Online at https://aerobasegroup.com/nsn/5910-01-064-9105         |
|---|
| Body Style:   |
| W/o mtg facilities terminal (s) on one surface                        |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 0.500 inches and 1.250 inches                                 |
| Body Length:  |
| 0.200 inches  |
| Body Width:   |
| 0.200 inches  |
| Body Height:  |
| 0.125 inches  |
| Center To Center Distance Between Terminals Parallel To Length:       |
| 0.250 inches  |
| Terminal Diameter:  |
| 0.020 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)                                   |
| Capacitance Value Per Section:  |
| 0.100 microfarads single section                                      |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -56.0/+22.0 without voltage applied single section                    |
| Nonderated Operating Temp:  |
| Between 10.0 degrees celsius and 85.0 degrees celsius                 |
| Nonderated Continuous Voltage Rating And Type Per Section:            |
| 50.0 dc single section  |
| Tolerance Range Per Section:  |
| -20.00/+80.00 percent single section                                  |
| Case Material:  |
| Plastic   |
| Insulation Resistance At Reference Temp:                              |
| 10000.0 megohms   |
| Dissipation Factor At Reference Tempurature In Percent:               |
| 3.0000  |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/o   |

**Unit Of Measure:** 

## NSN 5910-01-064-9105

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0