## NSN 5910-01-064-9110

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-064-9110 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.203 inches **Body Length:** 0.547 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 400.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 4.700 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Dc Leakage At Maximum Operating Temp: 0.2 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 0.100 microamperes **Terminal Surface Treatment:** Gold

**Plastic** 

**Case Insulation Material:** 

## NSN 5910-01-064-9110

Electrolytic Fixed Capacitor - Page 2 of 2



Pred	ious	Mater	ial And	d L	ocati	on:

Terminal surface gold and case silver

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A010b0