Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-064-9864

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.500 inches

Body Length:

0.560 inches

#### **Body Width:**

0.310 inches

**Body Height:** 

#### 0.190 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

**Terminal Diameter:** 

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

200.0 megohms

### Capacitance Value Per Section:

0.100 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

0.5000

### **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0