Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-065-6344

# Body Style:

W/o mtg facilities terminal (s) on one surface

# Mil-std-1276 Wire Lead Type Designator:

N-1

**Reliability Indicator:** 

Not established

### Terminal Length:

1.250 inches

**Body Length:** 

0.200 inches

#### **Body Width:**

0.200 inches

#### Body Height:

0.100 inches

#### Center To Center Distance Between Terminals Parallel To Length:

## 0.200 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

910.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

100000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

# Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0