NSN 5910-01-065-6350

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-065-6350 |
|---|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Length: |
| 0.175 inches |
| Body Width: |
| 0.070 inches |
| Body Height: |
| 0.120 inches |
| Terminal Diameter: |
| 0.010 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Solid |
| Electrical Polarization: |
| Nonpolarized |
| Capacitance Value Per Section: |
| 15.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 15.0 dc single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Capacitive Electrode Material: |
| Tantalum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 6.0000 |
| Dc Leakage At Reference Temp: |
| 0.500 microamperes |
| Terminal Surface Treatment: |
| Nickel |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-01-065-6350

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0